

ELA Offshore Cargo Carrying Units 10ft / 20ft

ela[container]



Brief description

The ELA Offshore Cargo Carrying Units are specially designed for offshore use and are applicable on all kinds of offshore units such as platforms, rigs, jack-up barges, accommodation barges, pontoons and all types of supply vessels.

Advantages of ELA Offshore Cargo Carrying Units:

- + available at short notice
- + easy handling due to standard measurements
- + different dimensions depending on your requirements
- + available for rent and sale
- + offshore certified slings included

Features

Certificates and Approvals

- + DNV 2.7-1 / EN 12079-1 / ISO 10855
- + ISO-Norm-R-668
- + CSC

10ft ELA Offshore Closed Top Container

L 2991 mm x W 2438 mm x H 2591 mm
L 20 ft x W 8 ft x H 8 ft 6 in



Configuration and features

Internal dimensions:
L 2802 mm x W 2288 mm x H 2238 mm
L 9 ft 2 in x W 7 ft 5 in x H 7 ft 3 in

Cubic Capacity: 14.3 m³ / 505 cu.ft

Tare weight: 2.2 t / 4,850 lbs.
MGW offshore: 10 t / 22,050 lbs.
Max Payload offshore: 7.8 t / 17,200 lbs.
MGW ISO: 10 t / 22,050 lbs.
Max. Payload ISO: 7.8 t / 17,200 lbs.

DNV certified slings included

20ft ELA Offshore Closed Top Container

L 6058 mm x W 2438 mm x H 2896 mm
L 20 ft x W 8 ft x H 9 ft 6 in



Configuration and features

Internal dimensions:
L 5836 mm x W 2218 mm x H 2468 mm
L 19 ft 1 in x W 7 ft 3 in x H 8 ft 1 in

Cubic Capacity: 31.9 m³ / 1126 cu.ft

Tare weight: 4.5 t / 9,960 lbs.
MGW offshore: 19.1 t / 42,040 lbs.
Max Payload offshore: 14.6 t / 32,080 lbs.
MGW ISO: 30.5 t / 67,200 lbs.
Max. Payload ISO: 26 t / 57,240 lbs.

DNV certified slings included

10ft ELA Offshore Open Top Container

L 2991 mm x W 2438 mm x H 2591 mm
L 10 ft x W 8 ft x H 8 ft 6 in



Configuration and features

Internal dimensions:
L 2800 mm x W 2240 mm x H 2360 mm
L 9 ft 2 in x W 7 ft 4 in x H 7 ft 8 in

Cubic Capacity: 14.8 m³ / 522 cu.ft

Tare weight: 2.1 t / 4,630 lbs.
MGW offshore: 9.9 t / 21,960 lbs.
Max Payload offshore: 7.8 t / 17,330 lbs.
MGW ISO: 10 t / 22,050 lbs.
Max. Payload ISO: 7.9 t / 17,420 lbs.

DNV certified slings included
Roof bows and tarpaulin fitted

20ft ELA Offshore Open Top Container

L 6058 mm x W 2438 mm x H 2591 mm
L 20 ft x W 8 ft x H 8 ft 6 in



Configuration and features

Internal dimensions:
L 5836 mm x W 2218 mm x H 2284 mm
L 19 ft 1 in x W 7 ft 3 in x H 7 ft 5 in

Cubic Capacity: 32.6 m³ / 1151 cu.ft

Tare weight: 3.7 t / 8,160 lbs.
MGW offshore: 19.7 t / 43,430 lbs.
Max Payload offshore: 16 t / 35,270 lbs.
MGW ISO: 30.5 t / 67,200 lbs.
Max. Payload ISO: 26.8 t / 59,040 lbs.

DNV certified slings included
Roof bows and tarpaulin fitted

10ft ELA Offshore Half Height Container

L 2991 mm x W 2438 mm x H 1280 mm
L 10 ft x W 8 ft x H 4 ft 2 in



Configuration and features

Internal dimensions:
L 2760 mm x W 2250 mm x H 990 mm
L 9 ft x W 7 ft 4 in x H 3 ft 3 in

Cubic Capacity: 5.92 m³ / 209 cu.ft

Tare weight: 1.7 t / 3,750 lbs.
MGW offshore: 11.7 t / 25,800 lbs.
Max Payload offshore: 10 t / 22,050 lbs.
MGW ISO: 11.7 t / 25,800 lbs.
Max. Payload ISO: 10 t / 22,050 lbs.

DNV certified slings included

20ft ELA Offshore Half Height Container

L 6058 mm x W 2438 mm x H 1280 mm
L 20 ft x W 8 ft x H 4 ft 2 in



Configuration and features

Internal dimensions:
L 5734 mm x W 2114 mm x H 892 mm
L 18 ft 8 in x W 7 ft x H 3 ft

Cubic Capacity: 10.8 m³ / 381 cu.ft

Tare weight: 3.4 t / 7450 lbs.
MGW offshore: 19.4 t / 42,720 lbs.
Max Payload offshore: 16 t / 35,270 lbs.
MGW ISO: 19.4 t / 42,720 lbs.
Max. Payload ISO: 16 t / 35,270 lbs.

DNV certified slings included

10ft ELA Offshore Reefer Container

L 2991 mm x W 2438 mm x H 2591 mm
L 10 ft x W 8 ft x H 8 ft 6 in



Configuration and features

Internal dimensions:

L 2343 mm x W 2290 mm x H 2172 mm
L 7 ft 7 in x W 7 ft 5 in x H 7 ft 1 in

Cubic Capacity: 11.6 m³ / 409 cu.ft

Tare weight: 2.8 t / 6,130 lbs. incl. Ref. Unit
MGW offshore: 10 t / 22,050 lbs.
Max Payload offshore: 7.2 t / 15,920 lbs.

Refrigeration:

Daikin, Carrier and Thermo King options

Set temperature range:

-25° C to +25° C with ambient to +50° C

DNV certified slings included

20ft ELA Offshore Reefer Container

L 6058 mm x W 2438 mm x H 2591 mm
L 20 ft x W 8 ft x H 8 ft 6 in



Configuration and features

Internal dimensions:

L 5049 mm x W 2280 mm x H 2260 mm
L 18 ft 7 in x W 7 ft 5 in x H 7 ft 6 in

Cubic Capacity: 27 m³ / 957 cu.ft

Tare weight: 5.1 t / 11,180 lbs.
MGW offshore: 20 t / 44,090 lbs.
Max Payload offshore: 14.9 t / 32,910 lbs.

Refrigeration:

Daikin, Carrier and Thermo King options

Set temperature range:

-25° C to +25° C with ambient to +50° C

DNV certified slings included

The data given on this datasheet are based on standard factory specifications but can be slightly different from one type to the other depending on the factory.